

MODEL TL-5955



International size reference: 2/3AA, ER14335

TECHNICAL DATA

(Typical values @+ 25°C for batteries stored for one year or less)



■ Nominal capacity @ 1.3 mA, to 2 V	1.5 Ah
■ Rated voltage	3.6 V
■ Maximum recommended continuous current	75 mA
■ Maximum pulse current capability	150 mA
■ Weight	12.5 g (0.441 oz)
■ Volume	5.2 cc
■ Operating temperature range	-55 °C to +85 °C
■ Li metal content	approx. 0.5 g
■ U.L. Component Recognition, MH 12193	

TADIRAN
LITHIUM
BATTERIES



TERMINATIONS & ORDERING NO.

SUFFIX- /S STANDARD	15-5955-21500
SUFFIX- /T SOLDER TABS	15-5955-31500
SUFFIX- /P AXIAL PINS	15-5955-41500
SUFFIX- /PT2 RADIAL PINS	15-5955-36500
SUFFIX- /TP POLARIZED TABS	15-5955-52500
SUFFIX- /PT POLARIZED TABS	15-5955-53500



iXtra - Long Term Hi **Performance**

Note: Any presentations in this data sheet concerning performance and are not construed as warranties either expressed or implied, of future performance.

大豪电子
 电话: 0755-83233025
<http://www.szdahao.com>
<http://www.very-tec.com>

and are not construed as warranties either expressed or implied, of future performance. ECN 1501879 Rev. D 11/08